



SCIU ASPEN

QUICK TECH INFO

Suspension System	Horst-link (four-bar)
Front Derailleur	No compatibility
Headset/Headtube	Semi integrated tapered SHIS ZS44/28.6 - ZS56/40
Seat Post	31.6mm
Seat Clamp	36.4mm
Length rear shock	205mm (eye to eye)
Stroke	65mm
Fork Compatibility	160-180mm
BB Shell	BSA 73mm
Max. Tire Size	Max Tire Clearance: 27,5"x3.0" or 29"x2.6" (May vary depending on tire manufacturer!!)
Max. Chainring Size	32t
Water Bottle Mounts	1
Shock Mounting Bushing	Top: Trunnion mount Shock. No extra Hardware! Bottom: Bushing 30x10 mm
Brake Mount	180 PM // Max Rotor 220mm
Fork Offset	44mm
Rear triangle spacing	Dropout Thru Axle: 12x148mm boost

Fahrwerk	Horst-link (Vier-Gelenker)
Umwerfer vorne	Nein
Steuersatz/Steuerrohr	Semi integriert tapered SHIS ZS44/28.6 - ZS56/40
Sattelstütze	31.6mm
Sattelklemme	36.4mm
Dämpferlänge	205mm (Auge-Auge)
Hub	65mm
Gabel-Kompatibilität	160-180mm
Tretlagergehäuse	BSA 73mm
Maximale Reifengröße	Max Reifen-Freiheit: 27,5"x3.0" or 29"x2.6" (Kann je nach Reifenhersteller variieren!!)
Max. Kettenblattgröße	32t
Wasserflaschenhalterungen	1
Stoßdämpferbefestigung	Oben: Trunnion mount Shock. Keine extra Hardware! Unten: Hülse 30 x 10 mm
Bremsaufnahme	180 PM // Max Rotor 220mm
Gabelversatz	44mm
Hinterbau-Breite	Dropout Thru Axle: 12x148mm boost